

KIMBER REFERENCE DESIGN



HIGH SECURITY MADE SIMPLE.

Kimber is a reference design tailored for host-based processing in an OEM product where a USB connection to the host system is preferred. This solution is a superior combination of optical and algorithmic elements that enable absolute security and unmatched security and ease-of-use. Kimber includes off-the-shelf near-infrared illumination, a commercially available image sensor, proprietary lensing for illumination and the image sensor, and leading-edge enrollment and authentication algorithms. On-board MIPI-TO-USB conversion enables communication from the host unit to Kimber via USB. Kimber was designed to allow easy integration into OEM units, and is easily customizable. The near-infrared illuminators are designed as "snap-offs" to facilitate custom placement within the OEM unit to help accommodate the volume available in the end-product. There are three different image sensor lensing options that allow nominal working distances between 30 cm and 60 cm with imager module thicknesses between 3.0 mm and 5.7 mm. Dual iris enrollment and single- or dual-iris authentication is supported with software and algorithms that are portable to the OS used in the OEM device.



THE GOLD STANDARD IN BIOMETRICS

- Every iris is unique - second only to DNA as a definitive identifier.
- Extremely high level of entropy prevents a stolen biometric template from being re-used.
- Single-iris False Match Rate of 1 in 1.5 million.
- Robust liveness detection.
- Anti-spoof protection.
- Enables identity certainty and data protection/integrity.

EyeLock is an acknowledged leader in advanced iris authentication for the Internet of Things (IoT). Our proprietary pulsed illumination method reduces power consumption, increases IR safety, and improves performance. EyeLock provides a whole system solution for iris authentication hardware, software, optics, algorithms, and backend matching.

KIMBER REFERENCE DESIGN

FEATURES

USABILITY

- "Arms-length" working distance.
- Works with eyeglasses.
- Works with most sunglasses.
- Works in daylight and darkness.
- Hygienic -- nothing to touch, no biometric left behind.
- Liveness testing and authentication in less than a second.

HARDWARE/MECHANICAL

- Near-infrared illumination LED(s)
- 5 megapixel monochrome imager with MIPI interface
- Optical solutions for nominal 30 cm, 45 cm, and 60 cm "Working Distance"
- Imager module thickness (z-dimension) 3.0 mm (30 cm), 4.1 mm (45 cm) and 5.7 mm (60 cm)
- USB system interface.

SECURITY

- Single iris False Match Rate (FMR) of 1 in 1.5 million.
- Optional dual-iris authentication.
- False Non Match Rate (FNMR) less than 2%.
- Robust liveness testing.
- Anti-spoof protection.
- Revocable/recallable biometric template.
- AES 256 encrypted biometric template.

SOFTWARE

- Portable to Linux, Android, Windows, and iOS.
- Flexible matching topologies: 1:1, 1:few, 1:many, local, network, cloud, multifactor.
- Algorithms are portable to a secure processing environment.
- Algorithms library available to support customer application creation.
- EyeLockApp: sample Java code available for streamlined customer software development.

SAFETY/COMPLIANCE

- IEC 62471:2006 & CIE S009/E-002 IR lamp safety standard.

APPLICATIONS / ENVIRONMENTS



LCD MONITORS



KEYBOARDS



P.O.S. DEVICES



VR HEADSET

FOR MORE INFORMATION, PLEASE CONTACT EYELock AT EMBEDDED_APPLICATIONS@EYELock.COM